

BUY ONLINE

FREE CATALOG

SAVE UP TO 25%



DATA BULLETIN

Outboard 100:1 Pre-Mix Synthetic 2-Stroke Oil

Performance-Engineered for Outboards

Specifically designed for outboard motors, Outboard 100:1 Pre-Mix Synthetic 2-Stroke Oil contains a heavy dose of low-temperature dispersant additives that excel at reducing varnish, carbon and deposits in water-cooled motors. Its low-smoke, low-odor, low-toxicity properties produce fewer emissions at 100:1 mix ratios than oils mixed at 50:1, benefitting operators and the environment. Outboard Synthetic 2-Stroke Oil is formulated to prevent "oil loading" and plug fouling for rapid throttle response, making it ideal for trolling motors.

AMSOIL Synthetic 2-Stroke Oil has been providing improved performance and protection in two-stroke engines since 1973. Trust the extensive experience of AMSOIL, The First in Synthetics®, to do the best job protecting your engine.

Engine Protection

Outboard Synthetic 2-Stroke Oil provides premium protection and performance at 100:1 mix ratios. It is formulated for hot-operating two-stroke outboard motors, effectively fighting carbon and deposit formation and preventing ring sticking.

Smokeless Operation

Outboard Synthetic 2-Stroke Oil's synthetic formulation burns cleanly. When mixed at 100:1, smoke is virtually undetectable. Boaters subjected to smoke and fumes benefit from these low-emission properties.



- **Excellent** lubricity and cleanliness properties
- **Controls** friction and helps prevent wear, plug fouling, ring sticking and exhaust port blocking
- **Improves** throttle response
- **Lowers or eliminates** smoke
- **Delivers** outstanding protection and performance at lean mix ratios
- **Anti-rust** formulation counteracts the damp environments often encountered in outboard applications

*All trademarked names and images are the property of their respective owners and may be registered marks in some countries. No affiliation or endorsement claim, express or implied, is made by their use. All products advertised here are developed by AMSOIL for use in the applications shown.

Order by Phone 1-800-956-5695 - Give Operator Reference #1702935

TYPICAL TECHNICAL PROPERTIES
Outboard Synthetic 2-Stroke Oil (ATO)

Table with 2 columns: Property and Value. Properties include Kinematic Viscosity @ 100°C, Kinematic Viscosity @ 40°C, Viscosity Index, Pour Point, Flash Point, and Fire Point.

APPLICATIONS

For pre-mix use in two-stroke outboard motors, personal watercraft and jet boats that specify TC-W3. For maximum performance, mix with gasoline at 100:1 regardless of the mix ratio specified for the equipment. Richer mix ratios may be used where desired.

Table with 3 columns: RATIO, OIL, and FUEL. Rows show mix ratios of 50:1, 80:1, and 100:1 with corresponding oil and fuel amounts.

WARRANTY SECURE®

Outboard Synthetic 2-Stroke Oil is Warranty Secure, keeping your factory warranty intact. Outboard Synthetic 2-Stroke Oil is a high-performance replacement for vehicle manufacturer-branded products and is also backed by the AMSOIL Limited Warranty (G1363). For details, visit www.amsoil.com/warrantysecure.



HEALTH & SAFETY

This product is not expected to cause health concerns when used for the intended application and according to the recommendations in the Safety Data Sheet (SDS). An SDS is available via the Internet at www.amsoil.com or upon request at (715) 392-7101. Keep Out of Reach of Children. Recycle used oil and bottle.



AMSOIL products and Dealership information are available from your local full-service AMSOIL Dealer.